



**LCD, 3600 lumens, WXGA, 28dB quiet operation,
long lamp replacement cycle**

PT-LW373

Designed for education and corporate applications

Key Features

LCD, 3600 lumens, WXGA

Lamp and filter replacement cycle of up to 10,000 hours
(Reduces TCO)

Quiet 28 dB Operation for Distraction - free Viewing

16,000:1 contrast ratio



PT-LW373

<https://eu.connect.panasonic.com/fi/en/products/projectors/pt-lw373>

| | |
|--|--|
| Power Supply | AC100-240V 3.5A 50/60 Hz |
| Power Consumption | 300W 6W when Standby mode set to Normal, 0.5W when Standby mode set to Eco*1 |
| LCD Panel Panel Size | 15.0 mm (0.59 inches) diagonal (16:10 aspect ratio) |
| LCD Panel Display Method | Transparent LCD panel (x 3, R/G/B) |
| LCD Panel Drive Method | Active matrix method |
| LCD Panel Pixels | 1,024,000 (1,280 x 800) x 3, total of 3,072,000 pixels |
| LCD Panel Pixel Configuration | Stripe |
| Lens | Manual zoom (1.2x), manual focus F 1.6- 1.76, f 19.16- 23.02 mm |
| Throw Ratio | 1.48- 1.78:1 |
| Lamp | 230 W UHM lamp |
| Lamp/Filter*2 Replacement Cycle | Normal: 5,000hrs / Eco1: 6,000hrs / Eco2: 10,000hrs |
| Screen Size | 30-300 inches (0.76 -7.62 m) diagonally, 16:10 aspect ratio |
| Colors | Full color (16,777,216 colors) |
| Brightness*3 | 3,600 lumens (lamp power: normal) |
| Center-to-Corner Uniformity*3 | 80% |
| Contrast*3 | 16,000:1 (all white/all black, Image mode:Dynamic, Lamp control: Normal, Iris: On) |
| Resolution | 1,280 x 800 pixels (Input signals that exceed this resolution will be converted to 1,280 x 800 pixels.) |
| Optical Axis Shift | 13:1(fixed) |
| Keystone Correction Range | Vertical: ±30°, horizontal: ±15° |
| Installation | Ceiling/floor, front/rear (menu selection) |
| Built-in Speaker Output Power | 10 W (monaural) x 1 |
| Terminals HDMI In | HDMI 19-pin x 1, HDCP and Deep Color compatible Audio signal: linear PCM (sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz) |
| Terminals Computer (RGB) 1 In | D-sub HD 15-pin (female) x 1 |
| Terminals Computer (RGB) 1 In R, G, B | R, G, B: 0.7 Vp-p, 75 ohms; HD/VD, SYNC: high impedance, TTL (positive/negative automatic) |
| Terminals Computer (RGB) 1 In Y, PB (CB), PR (CR) | Y: 1.0 Vp-p (including sync signal), 75 ohms PB (CB), PR (CR): 0.7 Vp-p, 75 ohms |
| Terminals Computer (RGB) 1 In S-Video | Y: 1.0 Vp-p; C: 0.286 Vp-p, 75 ohms |
| Terminals Computer (RGB) 2 In | D-sub HD 15-pin (female) x 1 |
| Terminals Computer (RGB) 2 In R, G, B | R, G, B: 0.7 Vp-p, 75 ohms; HD/VD, SYNC: TTL (positive/negative automatic) |
| Terminals Monitor Out | D-sub HD 15-pin (female) x 1 |
| Terminals Monitor Out R, G, B | R, G, B: 0.7 Vp-p, 75 ohms; HD/VD, SYNC: TTL (positive/negative polarity compatible) |
| Terminals Video In | Pin jack x 1, 1.0 Vp-p, 75 ohms |
| Terminals Audio In 1 | M3 (L, R) x 1, 0.5 Vrms |
| Terminals Audio In 2 | Pin jack x 2 (L, R x 1), 0.5 Vrms |
| Terminals Audio Out | M3 (L, R) x 1 (monitor out: 0- 2.0 Vrms, variable) |
| Terminals Serial In | D-sub 9-pin (female) x 1, for external control (RS-232C compliant) |
| Terminals LAN | RJ-45 x 1, for network connection, compliant with PLink™, 100Base-TX/10Base-T |
| Terminals USB | USB A (type A) connector x 1, for Memory Viewer/Wireless Module (Out put 5V MAX 500mA) USB B (type B) connector x 1, for USB Display |
| Power Cord Length | 1.8 m (5 ft 11 in) |
| Cabinet Materials | Molded plastic |
| Dimensions (W x H x D) | 335 x 96*4 x 252 mm (13-3/16 x 3-25/32*4 x 9-29/32 inches) |
| Weight*5 | Approx. 2.9 kg (6.4 lbs) |
| Operation Noise*3 | 37 dB (Lamp power: Normal), 33 dB (Lamp power: Eco1) 28 dB (Lamp power: Eco2) |

| | |
|------------------------------|---|
| Operating Temperature | 5°C-40°C (41°F-104°F) |
| | [at less than 1,400 m (4,593 ft.);[High land]:[off] |
| | 5°C-35°C (41°F-95°F) |
| | [at 1,400 m to 2,700 m (4,593 ft. to 8,858 ft.);[High land]:[on 1] |
| Operating Humidity | 5°C-30°C (41°F-86°F) |
| | [at 2,700 m to 3,000 m (8,858 ft. to 9,843 ft.);[High land]:[on 2] |
| Note | 20%-80% (no condensation) |
| | *1 When the Standby mode is set to Eco, network functions such as power on over the LAN network will not operate. Also, only certain commands can be received for external control using the serial terminal. |
| | *2 Usage environment affects the duration of filter. |
| | *3 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. |
| | *4 With legs at shortest position. |
| | *5 Average value. May differ depending on models. |
| | *6 Operation range differs depending on environments. |
| Brightness | 3600 lumens |
| Technology | LCD |